

1) CONSTRUCTION:

CONDUCTOR:	18 AWG STRANDED 7/.0152 BARE COPPER	NOM. DIA.	.046"
INSULATION:	POLYVINYLCHLORIDE, .016" NOM. WALL THICKNESS		.078"
TRIAD:	(3) INSULATED COLOR CODED SINGLES TWISTED TOGETHER TO FORM A CABLE CORE		.168"
SHIELD:	AN ALUMINIZED POLYESTER FOIL SHIELD (FOIL OUT, 100% COVERAGE) SHALL BE APPLIED OVER THE CABLE CORE AND SHALL CONTAIN A 20 AWG 7/28 STRANDED TINNED COPPER DRAIN WIRE IN CONTACT WITH THE METALIZED SURFACE FOR EASY TERMINATION.		.171"
JACKET:	POLYVINYLCHLORIDE, BLACK, .037" NOM. WALL THICKNESS	OVERALL CABLE DIAMETER	.245" (BY PI TAPE)

2) PHYSICAL PROPERTIES:

TEMPERATURE RATING, MAX.	80°C & 105°C
TEMPERATURE RATING, MIN.	-40°C
WT./M', NOM., NET.	39.6 LBS.
JACKET IS SUNLIGHT RESISTANT	

3) ELECTRICAL CHARACTERISTICS:

CAPACITANCE, MUTUAL, NOM.	31 PF/FT
CAPACITANCE, GROUNDED, NOM.	57 PF/FT
DIELECTRIC WITHSTANDING, MIN.	2000V RMS
VOLTAGE RATING, MAX.	300V
D.C. RESISTANCE, MAX.	6.64 Ω/1,000'

4) AGENCY APPROVALS:

- NEC (UL) TYPE PLTC
- NEC (UL) TYPE ITC
- NEC (UL) TYPE CM
- CEC C(UL) TYPE CM
- UL AWM STYLE 2464


5) APPLICATION:

PROCESS SYSTEM INTERCONNECT. POWER LIMITED TRAY CABLE, INSTRUMENTATION TRAY CABLE. CLASS 3 CIRCUITS. RoHS COMPLIANT MATERIALS.

6) PRINT: (WHITE INK)
 QUABBIN P/N 0342 (UL) TYPE PLTC OR ITC 18 AWG SHIELDED 105C SUN RES OR C(UL)US CM OR AWM 2464 -- RoHS --
(LOT DESIGNATOR)

7) COLOR CODE:
 TRIAD: BLACK X RED X WHITE

8) PACKAGING
 TO BE PACKAGED AS PER QWC'S
 STANDARD PACKAGING



Created 08/21/20	DRAWN: SGH 08/21/20	
REV. 01	CHECKED: ZRS 08/24/20	
TITLE 1 TRIAD (3/C) 18 AWG SHIELDED CABLE -- TYPE PLTC, TYPE ITC, TYPE CM, STYLE 2464		
QUABBIN P/N	0342	1 of 1

CUSTOMER APPROVAL:

DATE: