

- 1) CONSTRUCTION:
- | | | | |
|-------------|--|------------------------|-----------------------------------|
| CONDUCTOR: | 26 AWG 7/34 STRANDED TINNED COPPER | NOM. DIA. | .019" |
| INSULATION: | POLYOLEFIN, .010" NOM. WALL THICKNESS | .039" MAX. | |
| PAIRS: | COLOR CODED SINGLES TWISTED INTO PAIRS | .078" | |
| CABLE: | (4) TWISTED PAIRS TWISTED TOGETHER AND WRAPPED WITH A CLEAR POLYESTER BINDER TO FORM A CABLE CORE. | .162" | |
| SHIELDS: | AN OVERALL ALUMINIZED POLYESTER FOIL SHIELD (FOIL OUT, 100% COVERAGE) SHALL BE APPLIED OVER THE CABLE CORE AND SHALL CONTAIN A 26 AWG 7/34 STRANDED TINNED COPPER DRAIN WIRE IN CONTACT WITH THE METALIZED SURFACE. A SECOND SHIELD OF 38 AWG TINNED COPPER BRAID (85% MINIMUM COVERAGE), SHALL BE APPLIED OVER THE FOIL SHIELD. | .181" | |
| SEPARATOR: | A POLYESTER TAPE SEPARATOR SHALL BE APPLIED OVER THE SHIELDED CORE. | .184" | |
| JACKET: | POLYVINYLCHLORIDE, (COLOR, PER CHART 1), .022" NOM. WALL THICKNESS (PRESSURE) | OVERALL CABLE DIAMETER | .228" NOM. (± .010") (BY PI TAPE) |

- 2) PHYSICAL PROPERTIES:
- | | |
|--------------------------|-----------|
| TEMPERATURE RATING, MAX. | 75°C |
| TEMPERATURE RATING, MIN. | -20°C |
| WT./M', NOM., NET. | 33.4 LBS. |
- CHART 1:

QUABBIN P/N	JACKET COLOR
5739	BLACK
5740	BLUE
5741	TEAL

- 3) ELECTRICAL CHARACTERISTICS:
SEE PAGE 2


- 4) AGENCY APPROVALS:
NEC (UL) TYPE CMR
CEC C(UL) TYPE CMR

- 5) APPLICATION:
RoHS COMPLIANT MATERIALS.

- 6) PRINT: (WHITE INK ON BLACK JACKET, ALL OTHERS BLACK INK)
QUABBIN DATAMAX EXTREME DURABLE INDUSTRIAL ETHERNET PATCH CORD CAT 5e ScTP P/N (P/N PER CHART 1) -- C(UL)US TYPE CMR 4PR 26 AWG 75C -- RoHS -- (LOT DESIGNATOR) (SEQUENTIAL FOOTAGE)

- 7) COLOR CODE:
1. BLUE X WHITE/BLUE
 2. ORANGE X WHITE/ORANGE
 3. GREEN X WHITE/GREEN
 4. BROWN X WHITE/BROWN

- 8) PACKAGING:
TO BE PACKAGED AS PER QWC'S STANDARD PACKAGING



Created 1/9/13	DRAWN: 01/09/13	
REV. 01	CHECKED: 1/10/13	
TITLE		
DATAMAX EXTREME DURABLE INDUSTRIAL ETHERNET PATCH CABLE – 4 PR SCREENED		
DRAWING #	QWC0052	1 of 2


CUSTOMER APPROVAL:

DATE:

3) ELECTRICAL CHARACTERISTICS: (FOR 100m OF CABLE)

CAPACITANCE, MUTUAL, NOM.	13.5 PF/FT. AT 1 MHZ	
DIELECTRIC WITHSTANDING, MIN.	1500V RMS	
VOLTAGE RATING, MAX.	300V	
D.C. RESISTANCE, MAX.	42.6 Ω/1000'	
IMPEDANCE	100 +/- 15 Ω 1-100 MHZ	
IMPEDANCE, SMOOTHED	100 +/- 10 Ω TYPICAL 5 - 100 MHZ	
SRL	23 DB 1-20 MHZ	
	23 - 10 LOG(F/20) 20-100 MHZ	
RETURN LOSS	1 - 10 MHZ	20 + 5 LOG (F) DB MIN
	10 - 20 MHZ	25 DB MIN
	20 - 100 MHZ	25- 8.6 LOG(F/20) DB MIN
PS NEXT	1-100 MHZ	32.3 - 15 LOG (F/100) MIN
NEXT	1-100 MHZ	35.3 - 15 LOG (F/100) MIN
PSACRF	1-100 MHZ	20.8 - 20 LOG(F/100) MIN
ACRF	1-100 MHZ	23.8 - 20 LOG(F/100) MIN
ATTENUATION	1-100 MHZ	1.5[1.967 SQRT(F) + .023(F) + .05/SQRT(F)]MAX
DELAY	1-100 MHZ	534 + 36/SQRT(F)
DELAY SKEW	1-100 MHZ	<25NS
VELOCITY OF PROPAGATION	68%	

NOTE: ALL TESTING IS CONDUCTED OFF THE REEL.

Created 1/9/13	DRAWN: GBM 01/09/13	
REV. 01	CHECKED: JFR 1/10/13	
TITLE DATAMAX EXTREME DURABLE INDUSTRIAL ETHERNET PATCH CABLE - 4 PR SCREENED		
DRAWING #	QWC0052	2 of 2

CUSTOMER APPROVAL:

DATE: